



Rizer

Electric Aluminium Work Platform Single Mast



For further information on Standard Features & Options

CALL 1300 623 622



	MVP060E	MVP080E	MVP100E	MVP120E
S.W.L	150kg	150kg	150kg	136kg
Max. occupants	1	1	1	1
Working height	8.00m	10.00m	12.00m	14.00m
Platform floor height	6.00m	8.00m	10.00m	12.00m
Overall length(stowed)	1.27m	1.37m	1.43m	1.45m
Overall length(tilted back)	n / a	n / a	n / a	2.95m
Overall width	0.73m	0.73m	0.73m	0.73m
Overall height(stowed)	1.99m	1.99m	1.99m	2.77m
Overall height(tilted back)	n / a	n / a	n / a	1.95m
Outrigger footprint(l/w)	1.64/ 1.88m	1.64/ 1.88m	1.64/ 1.88m	1.92/ 2.16m
Platform size	0.69 X 0.60m	0.69 X 0.60m	0.69 X 0.60m	0.69 X 0.60m
Ground clearance	0.06m	0.06m	0.06m	0.06m
Up/Down speed	38/34 sec	41/32 sec	48/32 sec	62/46 sec
Lifting motor				
AC	110-230VAC/1.5kw	110-230VAC/1.5kw	110-230VAC/1.5kw	110-230VAC/1.5kw
DC	12VDC/1.5kw	12VDC/1.5kw	12VDC/1.5kw	12VDC/1.5kw
Tyres				
Back wheels	8in	8in	8in	8in
Front wheels	5in	5in	5in	5in
Weight	366(AC)/404(DC)kg	414(AC)/450(DC)kg	434(AC)/470(DC)kg	526(AC)/558(DC)kg

* Product specifications and prices are subject to change without notice or obligation
The photographs and/or drawings in this document are for illustrative purposes only